

**20.01.04 ALIMENTATORE PWM 220V/350mA CORRENTE COSTANTE**

■ DESCRIZIONE

- ALIMENTATORE A CORRENTE COSTANTE PER LED
- UTILIZZO INDOOR
- COMPONENTE LEAD FREE

■ SPECIFICHE TECNICHE ELETTRICHE

- INPUT VOLTAGE 200-240Vac 50Hz
- INPUT RANGE VOLTAGE 180-264Vac 50Hz
- INPUT CURRENT 0,15Amps at 4 pcs LED
- NO LOAD OUTPUT VOLTAGE 18V ±10%
- OUTPUT VOLTAGE (1 LED) 3~4V TYP.
- FULL LOAD OUTPUT CURRENT (CONSTANT CURRENT) 350mA±7,5%
- OVER CURRENT PROTECTION
- SHORT CIRCUIT PROTECTION

■ SPECIFICHE TECNICHE MECCANICHE

- DIMENSIONS 42,2(L) \* 40,2(W) \* 22(H)mm (Tolerance as drawing)
- WEIGHT 45g Max.
- OPERATING TEMPERATURE 0°C to 50°C
- STORAGE TEMPERATURE -20°C to 60°C
- RELATIVE TEMPERATURE 40°C ± 2°C
- MTBF 50,000 hrs to MIL-HDBK-217F

■ STANDARD

- SAFTY EN61558-1, EN6158-2-17
- EMC EN55014-1, EN55014-2, EN61000-3-2, EN61000-3-3

